

Your configured drive



ACS880-01

- Direct torque control (DTC) for precise open and closed loop control
- Built-in safety features for simplified configuration
- Energy optimizer and energy efficiency information for monitoring and saving energy
- Communication with all major automation networks

ACS880-01-363A-3+D150+E201+E208

Product details

Input voltage	380-415 V
Heat loss	4800 W
Frame size	R9
Noise level	68 dBA

Light overload use(I_{LD} , P_{LD})	345 A, 200 kW
Air flow	1150 m ³ /h
Nominal output (I_N , P_N)	363 A, 200 kW
Type code	ACS880-01-363A-3+D150+E201+E208
Standard Features	Wall mounted IP 21 (UL type 1) Assistant control panel with Bluetooth, ACS-AP-W Inbuild choke Primary control program Safe torque off Cable lead through entry Coated boards Quick guides with default set of languages 6-pulse supply DTC control
Maximum output current (I_{MAX})	498 A
Heavy-duty use(I_{HD} , P_{HD})	293 A, 160 kW
Net Weight	95 kg
Dimensions (HxWxD)	955x380x413 mm

Selected configuration options

D150 Braking chopper

E201 EMC/RFI-filter, Cat. C3, 2nd Env., Unearthed Network (IT)

E208 Common mode filter

Documents

[!\[\]\(3211b5d1d968fc1665909b34f9f16010_img.jpg\) Download Hardware Manual](#)

[!\[\]\(6059a5aa8b4ca7bb793408023d6c6e42_img.jpg\) Download Firmware Manual](#)

[!\[\]\(c50c8b7b2cc2cf9ff925edec0ee94c0d_img.jpg\) View catalog](#)

[!\[\]\(6a9b39b98eb945faa14c645ec99e4eaa_img.jpg\) Open product page](#)

[Acceptable Use Policy](#)

[Privacy Notice](#)

[Legal](#)

[Version 3.6.0](#)

[Change cookie settings](#)

© Copyright 2024 ABB