

fixed-mounted molded case circuit breaker frame 1600; with RTC and 4AUX trip alarm switch S24; Icu "M" Icu=55kA @ 415V, 3-pole ETU350, LSI, In=1600A rotary coding switch Ir=640...1600A Isd=1...10xIn, li=1.5...15xIn N conductor protec. adjustable opt. w. ext. CT; up to 200% nut keeper kit

Model	
product brand name	SENTRON
product designation	Molded case circuit breaker
design of the product	MCCB
design of the actuating element	spring actuator
type of the driving mechanism	without motor drive
type of the driving mechanism / motor drive	No
design of the overcurrent release	ETU350
General technical data	
number of poles	3
size of the circuit-breaker	1600 A
mechanical service life (switching cycles) / typical	1 000
circuit-breaker / Design	3VA2
Voltage	
insulation voltage / rated value	1 000 V
operating voltage / at AC / at 50/60 Hz / rated value	690 V
protection class IP	IP20
protection class IP / on the front	IP20
protection function of the overcurrent release	LSI
power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	77 W
Current	
continuous current / rated value	1 600 A
adjustable current response value current	
• of the current-dependent overload release / full-scale value	1 600 A
• of instantaneous short-circuit trip unit / initial value	2 400 A
• of instantaneous short-circuit trip unit / full-scale value	24 000 A
short-time withstand current (Icw)	
• limited to 1 s / rated value	20 kA
• at AC / at 415 V / limited to 0.5 s / rated value	20 kA
Main circuit	
operational current	
• at 40 °C / rated value	1 600 A
• at 50 °C / rated value	1 481 A
• at 55 °C / rated value	1 417 A
• at 60 °C / rated value	1 352 A
• at 65 °C / rated value	1 281 A
• at 70 °C / rated value	1 209 A
Auxiliary circuit	
number of CO contacts / for auxiliary contacts	4
Suitability	
suitability for use	system protection
Adjustable parameters	
adjustable current response value current	

<ul style="list-style-type: none"> • of the short-time delayed short-circuit release / initial value 	1 600 A
<ul style="list-style-type: none"> • of the short-time delayed short-circuit release / full-scale value 	16 000 A
adjustable current response value current / of the current-dependent overload release / initial value	640 A
product component	
<ul style="list-style-type: none"> • trip indicator 	Yes
<ul style="list-style-type: none"> • voltage trigger 	No
<ul style="list-style-type: none"> • undervoltage release 	No
product extension / optional / motor drive	Yes

Product function

product function	
<ul style="list-style-type: none"> • grounding protection 	No

Display and operation

display version	Without display
-----------------	-----------------

Short circuit

breaking capacity operating short-circuit current (Ics)	
<ul style="list-style-type: none"> • at 415 V / rated value 	55 kA
<ul style="list-style-type: none"> • at 500 V / rated value 	36 kA
<ul style="list-style-type: none"> • at 690 V / rated value 	25 kA
breaking capacity maximum short-circuit current (Icu)	
<ul style="list-style-type: none"> • at 415 V / rated value 	55 kA
<ul style="list-style-type: none"> • at 440 V / rated value 	55 kA
<ul style="list-style-type: none"> • at 500 V / rated value 	36 kA
<ul style="list-style-type: none"> • at 690 V / rated value 	25 kA

Connections

arrangement of electrical connectors / for main current circuit	Main connection on front side
type of electrical connection / for main current circuit	busbar connection

Mechanical Design

height	296 mm
width	210 mm
depth	183 mm
fastening method	fixed mounting
net weight	14 kg

Environmental conditions

ambient temperature / during operation	
<ul style="list-style-type: none"> • minimum 	-25 °C
<ul style="list-style-type: none"> • maximum 	70 °C
ambient temperature / during storage	
<ul style="list-style-type: none"> • minimum 	-40 °C
<ul style="list-style-type: none"> • maximum 	70 °C

Certificates

reference code	
<ul style="list-style-type: none"> • acc. to DIN EN 61346-2 	Q
<ul style="list-style-type: none"> • acc. to IEC 81346-2 	Q

Further information

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA2716-1AC03-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VA2716-1AC03-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA2716-1AC03-0AA0

Tender specifications

<http://www.siemens.com/specifications>





last modified:

3/16/2020 